

# Single wall insert with foldable rubber sleeve

for setting in concrete and connecting cable ducts

## HSI150 1x1 KMA172/400

Article no.: 3030477600, GTIN: 4052487242172



- thanks to the folding sleeve technique, no additional pipe connection components are necessary
- elastic and firmly supported connection due to increased insertion depth, even with deflection of the cable duct
- inside connection option for system seals for cables



Picture may differ from selected product

For the direct connection of cable ducts (exterior) and for connecting system seals for cables (interior).

## FACTS

### Advantages:

- defined insertion depth of the cable duct through the stop in the sleeve
- Available from wall thicknesses of 120 mm and above
- Quality seal: tightness from the factory. Option to check for accidental or unauthorized opening of the closing cover
- pressure-tight seal to the concrete through 3-ribbed seal, with two 3-ribbed seals from wall thicknesses of 150 mm and above



## Scope of delivery:

- 1 piece pressure-tight system cover HSI150 DTS
- 1 piece blind cover
- 2 pieces of HSI150 AH40 spacer
- 1 piece of clamping strap
- when connecting corrugated cable ducts, clip rings must be ordered separately. When ordering, please specify duct type and manufacturer.

## Dimensions:

- Frame dimensions: 220x 220 mm
- Centre distance with spacer: 250 mm

## Properties:

- FHRK-certified

## Application range:

- Waterproof concrete stress class 1 and 2

## Material:

- Wall insert: ABS with TPE 3-ribbed seal
- Closing cover: ABS with TPE seal
- Adapter pipe: PVC
- Sleeve: EPDM
- Clamping straps: W4
- Blind cover: PP

## Tightness:

- gastight and watertight to 2.5 bar
- radon-proof

## FEATURES

:	400
Pipe	
OD:	160-172

## PICTURES

