

Membrane injection system


for buildings without a basement

2LINE MIS25 1x6-13 PRO

: 3030477964, GTIN: 4052487242905



- **Controlled RESINATOR resin discharge thanks to proven membrane injection system**
- **Tool-free assembly with RESINATOR double syringe**
- **Horizontal or inclined installation up to 45° inclination**



For reliable sealing of fibre optic cables.

Advantages:

- Sealing in all common wall types (DIN 18533/WU concrete)
- Minimum RESINATOR resin quantity thanks to adhesive collar
- Small opening diameter Øi 25 mm
- Quick to assemble in just a few minutes

Scope of delivery:

- 1 piece 2LINE MIS25
- 1 piece RESINATOR dual syringe, 25 ml
- 1 piece wall terminator element

Dimensions:

- Area of application: 1 fibre-optic cable with Øa 6 - 13 mm
- for drill holes Øi: 25 mm
- for wall thicknesses starting from 150 mm

Application range:

- DIN 18533 W1-E, DIN 18533 W2.1-E
- Waterproof concrete stress class 1, waterproof concrete stress class 2
- 1 fibre-optic cable with Øa 6 - 13 mm

Material:

- Membrane sleeve: TPE
- Foil flange: Aluminium-plastic composite foil with butyl rubber
- Wall terminator element: PCFR

Tightness:

- gastight and watertight to 1.0 bar

Number of cables/medium: 1
Suitable for medium pipe OD (mm): 6-13 MM

