

# Membrane injection system

## for buildings without a basement

### MIS60S E BL1300 SET1

Article no.: 3030453466, GTIN: 4052487240024



- **universal building entry with membrane injection system for sloping drill holes through floor slabs or walls**
- **controlled ejection of resin through slit membrane hose**
- **sealing lips ensure gentle seal for media lines**



Picture may differ from selected product

Suitable for sloping entry through the wall or floor slab.

## FACTS

### Advantages:

- Quick to assemble in just a few minutes
- Not necessary to restore basement seal to DIN 18533
- Variety of pre-mounted seal inserts for variable configuration

### Scope of delivery:

- 10 pieces of MIS 60S
- 1 piece of wall terminator element
- 10 pieces of wall collar (only with electricity variant)
- 10 pieces 2-component resin Resinator, 150 ml

## Dimensions:

- For core drills Ø: 62 - 65 mm
- Overall length: 1300 mm

## Application range:

- Water exposure class DIN 18533: W1-E
- Waterproof concrete stress class 1, waterproof concrete stress class 2

## Material:

- Flange, seal insert, counter-bearing and adapter: EPDM
- Resin filler hose: PE
- Wall collar: PE
- Pipe: PVC-U
- Wall terminator element: Flame-retardant polycarbonate

## Tightness:


- gastight and watertight to 1.0 bar

## FEATURES

Number of cables/medium:  
suitable for medium pipe OD  
(mm):

1  
1  
1  
3  
4  
24-30  
18-24  
12-18  
6-12  
10  
5-7

## PICTURES



## ACCESSORIES REQUIRED



Cartridge gun



Quick tensioning device