

Standard press seal

with graduated super segmented ring technology

HSD100 SSG 1x25/32/40/50/63 b40 A2/EPDM

Article no.: 3030300058, GTIN: 4052487121286



- **optical and tangible installation security due to integrated control opening**
- **integrated super segmented ring technology for individual adjustment to cable diameter on site**
- **segments with exact diameter marking**

For sealing of newly to install pipes or already installed pipes inside core drilled holes or wall sleeves. Can be adapted to the most common cable diameters on site.



Picture may differ from selected product

FACTS

Advantages:

- Split as standard \varnothing 100 mm
- Can be split on site at and above \varnothing 150 mm for retrofit installation
- All manner of material combinations are available for tailor-made applications
- available from stock

Dimensions:

- Sealing width: 40 mm

Properties:

- FHRK-certified
- U-profile: maximum stability for press segments



Application range:

- Waterproof concrete stress class 1, waterproof concrete stress class 2

Material:

- Press plates, screws and nuts: rust-free stainless steel V2A (AISI 304L) or V4A (AISI 316L)
- Rubber: EPDM

Tightness:

- gastight and watertight
- radon tight

FEATURES

Wall sleeve/core drilled hole ID (mm):	100
Openings:	1
Carrier pipe \varnothing_a (mm):	25/32/40/50/63
Packing unit:	1

PICTURES

