

# Standard press seal

with graduated super segmented ring technology

## HSD150 SSG 1x75/90/110 b40 A2/EPDM

: 3030300062, GTIN: 4052487121804



- **optical and tangible installation security due to integrated control opening**
- **Integrated super segmented ring technology for individual adjustment to cable diameter on site**
- **Segments with exact diameter marking**



For sealing of newly to install pipes or already installed pipes inside core drilled holes or wall sleeves. Can be adapted to the most common cable diameters on site.

### Advantages:

- Split as standard Ø 100 mm
- Can be split on site at and above Ø 150 mm for retrofit installation
- All manner of material combinations are available for tailor-made applications
- Available from stock



### Dimensions:

- Sealing width: 40 mm

### Properties:

- FHRK-certified
- U-profile: maximum stability for press segments

## Application range:

- Waterproof concrete stress class 1, waterproof concrete stress class 2

## Material:

- Press plates, screws and nuts: rust-free stainless steel V2A (AISI 304L) or V4A (AISI 316L)
- Rubber: EPDM

## Tightness:

- gastight and watertight
- radon tight

|  |           |
|--|-----------|
| Wall sleeve/core drilled hole ID (mm): | 150       |
| Openings:                              | 1         |
| Carrier pipe $\varnothing_a$ (mm):     | 75/90/110 |
| Packing unit:                          | 1         |

