# Fire protection kit S90

## For core drills and wall sleeves

## HSS100 KB FR HRD

Article no.: 5030010032, GTIN: 4052487233569

- **special assembly pockets for the assembly of pads on one side**
- **special assembly pockets for the assembly of pads on one side**

Gastight and watertight fire barrier meeting the requirements of fire resistance class S90 in accordance with DIN 4102-9 for installation in core drills and/or plastic wall sleeves for walls. The seal is created with the HRD press seal. The barrier is approved for use with all types of cable in wall openings up to Ø 300 mm.

Picture may differ from selected product

# FACTS

## Advantages:

- High degree of flexibility as regards subsequent assignment
- No additional wall attachments necessary
- No limits on individual cable diameters
- Weatherproof fire-stop pads

## Scope of delivery:

- Wall openings up to Ø 100 mm: 1 set of HVS pads for full assignment (without cable): 2x HVS-K-250, 3x HVS-KB-60
- Wall openings up to Ø 150 mm: 1 set of HVS pads for full assignment (without cable): 2x HVS-K-400, 3x HVS-K-250, 3x HVS-KB-60
- Stainless steel clamping strap
- 1 piece of Identification sign

## Dimensions:

- Barrier thickness: min. 280 mm
- Wall thickness at and above: 150 mm
- For core drills ID: 70 - 300 mm
- For plastic wall sleeves ID: 80 - 300 mm

## Tests/Standards:

- DIBT approval Z-19.15-1906 to DIN 4102-9

# FEATURES

| | |
|---|---|
| Wall sleeve/core drilled hole ID (mm): | 100 |

# PICTURES

# ACCESSORIES REQUIRED

Lubricant

Assembly plate for fire-stop pads

Hauff-Technik GmbH & Co. KG
Robert-Bosch-Straße 9
89568 Hermaringen, GERMANY

Tel. +49 7322 1333-0
Fax +49 7322 1333-999

office@hauff-technik.de