

# Standard press seal

## for rainwater utilisation systems

### HSD100 RW 1x25/32/40+3x6-18 b40 A2/EPDM

Article no.: 3030300059, GTIN: 4052487223720



- **optical and tangible installation security due to integrated control opening**
- **integrated segmented ring technology for individual adjustment to cable diameters on site**

For sealing new media pipes/cables to be installed or media pipes/cables that have already been laid in core drills or wall sleeves, specially adapted for rainwater utilisation systems.



Picture may differ from selected product

## FACTS

### Advantages:

- Split as standard for retrofit installation
- available from stock

### Scope of delivery:

- 1 packing unit: 5 items

### Dimensions:

- Sealing width: 40 mm
- For core drills/wall sleeves  $\varnothing$ : 100 mm
- For 4 cables/pipes of which 3 x  $\varnothing$  6-18 mm and 1 x  $\varnothing$  25, 32 or 40 mm



## Properties:

- FHRK-certified
- U-profile: maximum stability for press segments

## Application range:

- Waterproof concrete stress class 1, waterproof concrete stress class 2

## Material:

- Press plates, screws and nuts: rust-free stainless steel V2A (AISI 304L)
- Rubber: EPDM

## Tightness:

- gastight and watertight
- radon tight

## FEATURES

|  |                  |
|--|------------------|
| Wall sleeve/core drilled hole ID (mm): | 100              |
| Number of cables/medium overall:       | 4                |
| Number of cables/medium:               | 1<br>3           |
| suitable for medium pipe OD (mm):      | 25/32/40<br>6-18 |
| Packing unit:                          | 5                |

## PICTURES

