

Standard press seal

for building connections

HSD100 EW 1x24-44+4x7-12 b40 A2/EPDM

Article no.: 3030300054, GTIN: 4052487221566



- **optical and tangible installation security due to integrated control opening**
- **integrated segmented ring technology for individual adjustment to cable diameters on site**

For sealing a water line or a power cable and communications lines in core drills or wall sleeves.



Picture may differ from selected product

FACTS

Advantages:

- available from stock

Scope of delivery:

- 1 packing unit: 15 items

Dimensions:

- Sealing width: 40 mm
- For core drills/wall sleeves \varnothing : 100 mm
- For 5 cables/pipes of which 4 x \varnothing 7-12 mm and 1 x \varnothing 24-44 mm



Properties:

- FHRK-certified
- U-profile: maximum stability for press segments

Application range:

- Waterproof concrete stress class 1, waterproof concrete stress class 2

Material:

- Press plates, screws and nuts: rust-free stainless steel V2A (AISI 304L)
- Rubber: EPDM

Tightness:

- gastight and watertight
- radon tight

FEATURES

Wall sleeve/core drilled hole ID (mm):	100
Number of cables/medium overall:	5
Number of cables/medium:	1 >4
suitable for medium pipe OD (mm):	24-44 >7-12
Packing unit:	15

PICTURES

