

# Customized press seal

with segmented ring technology

## HRD150/160 SGI b60



- **tailor-made to meet requirements**
- **segmented ring technology for adjustment to three or five different pipe diameters on site**
- **form-locked connection to bayonet, therefore integrated tear-out protection**
- **also suitable for sealing TRI-Delta cables**

For use in wall insert and plastic flange HSI150. Split design for sealing new cables to be installed or cables that have already been laid and various frequently recurring cable configurations. The individual seal with segmented rings enables the cable diameter to be adjusted on site. A number of individual seals can be replaced by a single universal seal.



Picture may differ from selected product

## FACTS

### Advantages:

- Unused openings factory-sealed with blind plugs
- split seal for retrofit installation

### Scope of delivery:

- Blind plugs
- 1 lubricant stick
- Minimum purchasing quantity: 25 pieces of



## Dimensions:

- Sealing width: 60 mm
- Press plates: 5 mm
- OD: 150 /160 mm

## Properties:

- Minimum purchasing quantity: 25 pieces of

## Material:

- Press plates, screws, nuts and washers: rust-free stainless steel V2A (AISI 304L) or V4A (AISI 316L)
- Rubber: EPDM

## Tightness:

- gastight and watertight
- Radon-proof

## PICTURES

