

# Tundish

## AT110

: 827001601, GTIN: 4052487171663



- **With axial tolerance compensation**
- **easy integration of the vapour barrier using the adhesive ribbon**
- **Non-trip installation according to DGUV 38 §12a thanks to step safe insert**
- **With integrated level for position alignment of the tundish**



Tundish with integrated step protection insert for setting base slab in concrete for optimum sealing to the underground sewer pipe. To compensate an offset (after concreting) between downpipe and base drain in any direction.

### Advantages:

- Saves rectangular recesses and therefore complex follow-up work
- quick and easy installation
- Gas-tight and watertight connection to the base slab thanks to the integrated 3-ribbed seal
- TPE sealing lips to seal underground sewage pipe
- Step safe insert with perforation and dirt trap grooves can be used during construction to drain the base slab
- Undercut for optimum fixing in concrete



### Scope of delivery:

- 1 piece Clamping strap
- 1 piece Step safe insert

## Dimensions:

- Diameter: 385 mm
- for underground sewage pipe Ø 110 mm

## Properties:

- Built-in stop in tundish for exact pipe positioning
- 50-mm surrounding flange for connecting the vapour barrier

## Application range:

- DIN 18533 W1-E
- Waterproof concrete stress class 1, waterproof concrete stress class 2

## Material:

- Step safe insert: PP
- Funnel: ABS/TPE

## Tightness:

- gastight and watertight
- radon tight

## Tests/Standards:

- KG 2000 pipes to DIN EN 14758
- KG pipes to DIN EN 13476-2

Suitable for medium pipe OD 110  
(mm):  
Packing unit: 1

