

Standard press seal

with super segmented ring technology and polymer press plates

HRK100 SSG 1x18-65 b40 PAGF/A4/EPDM55

: 3030300044, GTIN: 4052487223591



- **Integrated segmented ring technology for individual adjustment to cable diameters on site**

- **Press plates have form-fit connections**

For sealing a water line or a power cable and communications lines in core drills or wall sleeves. Split design for sealing new cables to be installed or cables that have already been laid.



Advantages:

- Available from stock

Scope of delivery:

- Blind plug (if there is more than one cable entry)
- 1 piece Knife
- 1 piece Lubricating stick

Dimensions:

- Sealing width: 40 mm

Properties:

- FHRK-certified



Application range:

- DIN 18533 W1-E, DIN 18533 W2.1-E, DIN 18533 W2.2-E
- Waterproof concrete stress class 1, waterproof concrete stress class 2

Material:

- Press plates: glass fibre reinforced polyamide
- Rubber: EPDM
- Screws and nuts: rust-free stainless steel V4A (AISI 316L)

Tightness:

- gastight and watertight
- radon tight

| | |
|--|-------|
| Wall sleeve/core drilled hole ID (mm): | 100 |
| Openings: | 1 |
| Carrier pipe \varnothing_a (mm): | 18-65 |
| Packing unit: | 9 |

