

Fixed/loose flange wall sleeve made from stainless steel

for setting in concrete for black tank according to DIN 18533

FLFE1x400/0/500 DIN18533 A2

: 2500400500

For setting in concrete or mortar in walls, ceilings or floors.



Advantages:

- Tailor-made designs can also be produced
- Also available with multiple entries and in a variety of diameters
- Installation flush with formwork

Scope of delivery:

- 1 piece Fixed/loose flange wall sleeve
- Bolts and nuts M20 (DIN 18533)
- With closing covers on both sides

Dimensions:

- Standard fixed flange $\varnothing a$ equal to the relevant wall sleeve $\varnothing i$ + approx. 330 mm (for one passage)

Application range:

- DIN 18533 W2.1-E, DIN 18533 W2.2-E

Material:

- Fixed/loose flange wall sleeve: stainless steel V2A (AISI 304L) or V4A (AISI 316L)
- Closing cover: PE

Tightness:

- gastight and watertight

| | |
|------------------------------------|-----|
| Wall sleeve ID (mm) D1: | 400 |
| Fixed flange OD (mm) D2: | 730 |
| Loose flange OD (mm) D3: | 720 |
| Wall sleeve wall thickness (mm) S: | 3 |
| wall thickness (mm): | 500 |





Rubber inlays