


ETGAR building package for single-line building service outlets

for buildings with a basement

HAW-E ETGAR BHP

: 3030458216, GTIN: 4052487239974



For routing and distributing electric power and communication lines from the building to the property's surrounding grounds. For installation in a universal MSH Basic-FUBO-E wall sleeve.



Advantages:

- Complete package with connection options for the ETGAR corrugated pipe
- Combinable with the products of the ETGAR garden distribution range
- Visual and tangible installation reliability thanks to built-in inspection openings

Scope of delivery:

- Basic component for installation in universal wall sleeve UFR100/x
- Outer sealing element for installation in wall sleeve.
- Insulating plate for integrating the building insulation in the area of the building services outlet
- 1 piece ETGAR sealing element 1x26-30+3x5-8+2x7-13
- 4-piece corrugated pipe connection set (1 double sleeve DN 75 + 3 profile seals DN 75) RAS4

Dimensions:

- Compatible with UFR wall sleeve, ID: 100 mm
- maximum wall thickness: 500 mm

Application range:

- DIN 18533 W1-E, DIN 18533 W2.1-E
- Waterproof concrete stress class 1, waterproof concrete stress class 2

Tightness:

• gastight and watertight to 1.0 bar

Packing unit: 10



Universal wall sleeve

Tel. +49 7322 1333-0

Fax +49 7322 1333-999