Single wall insert with foldable rubber sleeve

for setting in concrete and connecting corrugated cable ducts

HSI150 1X1 KMA172/120

Article no.: 3030476250, GTIN: 4052487242103

Picture may differ from selected product

- **thanks to the folding sleeve method, no additional pipe components are required**
- **elastic and firmly anchored connection thanks to increased insertion depth, even if the cable duct hose is deflected**
- **inside connection option for system seals for cables**

For the direct connection of cable protection conduits (outside) and for connecting system seals for cables (inside).

FACTS

Advantages:

- defined insertion depth of the cable duct hose through stop in the sleeve
- readily available for wall thicknesses 120 mm and above
- quality mark: sealed ex works. Option to check for accidental or unauthorised opening of the closing cover
- pressure-tight seal to the concrete through 3-ribbed seal, with two 3-ribbed seals from wall thicknesses of 150 mm and above

Scope of delivery:

- 1 piece of pressure-tight system cover HSI150 DTS
- 1 piece of blind cover
- 2 pieces of HSI150 AH40 spacer
- 1 piece of clamping strap
- when connecting corrugated cable ducts, clip rings must be ordered separately. When ordering, please specify tube type and producer.

Dimensions:

- Frame dimensions: 220x 220 mm
- Centre distance with spacer: 250 mm

Properties:

- FHRK-certified

Application range:

- Waterproof concrete stress class 1, waterproof concrete stress class 2

Material:

- Wall insert: ABS with TPE 3-ribbed seal
- Closing cover: ABS with TPE seal
- Adapter pipe: PVC
- Sleeve: EPDM
- Clamping straps: W4
- Blind cover: PP

Tightness:

- gastight and watertight to 2.5 bar
- radon tight

FEATURES

wall thickness (mm):	120
Pipe OD:	172

PICTURES

Hauff-Technik GmbH & Co. KG
Robert-Bosch-Straße 9
89568 Hermaringen, GERMANY

Tel. +49 7322 1333-0
Fax +49 7322 1333-999

office@hauff-technik.de