


Multi-line building package

for buildings with a basement

MSH PolySafe BHP

Article no.: 3030476028, GTIN: 4052487240949



- with integrated spirit level
- optical and tangible installation security due to integrated control opening

For the collective feeding in and sealing of all supply lines (power, water, telecommunications, gas).



Picture may differ from selected product

FACTS

Advantages:

- Seals all supply lines through one entry
- Continuous duct connection up to the main supply lines at the edge of the property possible
- All services are fed in and sealed separately
- The arrangement of the individual services is flexible



Scope of delivery:

- 1 piece Multi-line building entry system MSH PolySafe GV1
- 1 piece External sealing element MSH PolySafe M6.2
- 1 piece insulation disc MSH PolySafe M3
- 1 piece sealing element for drinking water SDW 1x32/40/50
- 1 piece sealing element for electricity SDE 1x26-29/36-39/43-46/48-51
- 1 piece Universal sealing element communications SDK 1x13-21+3x7-13+1x5-13
- 1 piece blind sealing element SD0
- 1 piece 16-piece pipe connection set (4 double sleeves DN75 + 12 profile seals DN75) RAS16
- 2 pieces sleeve caps MS78U 1x24-52 for electricity and water
- 1 piece sleeve cap MS78K 1x13-21+3x7-13+1x5-12 for communications
- 1 piece sleeve cap MS78 D0 for blind seal
- 2 pieces GMT35 lubricant

Dimensions:

- Compatible with core drill/wall sleeve: ID: 199 203 mm
- Maximum wall thickness: 500 mm (special lengths on request)

Properties:

• DVGW-certified

Application range:

- DIN 18533 W1-E, DIN 18533 W2.1-E
- Waterproof concrete stress class 1, waterproof concrete stress class 2

Tightness:

- gastight and watertight to 1.0 bar
- radon tight


Tests/Standards:

• DVGW VP 601

FEATURES

Packing unit: 6

PICTURES



Tel. +4973221333-0 Fax +4973221333-999 office@hauff-technik.de