Seal insert for basic insert

arranged side by side

MSH Basic MBK SR3

Article no.: 3030484493, GTIN: 4052487242967

- **all-around smooth surface for optimum connection of the finished flooring**

For the collective feeding in and sealing of all supply lines (power, water, telecommunications, gas) for buildings without a basement, for installation in MSH Basic FUBO EBT SR3 body. The MSH Basic MBK SR3 is supplemented with a closed sealing element which is available to purchase separately.

Picture may differ from selected product

FACTS

Advantages:

- Seals all supply lines through one entry
- All services are sealed separately
- The arrangement of the individual services is flexible

Scope of delivery:

- 1 piece of seal insert
- 2 pieces of nail screws for attaching the seal insert
- 6 pieces of self-tapping screws 8x35 for sealing service lines

Dimensions:

- Width: 379 mm
- Length: 135 mm
- Height: 283 mm

Properties:

- DVGW-certified
- Also required: closed sealing elements

Material:

- Anchor plate: glass fibre reinforced polyamide
- Pipes: ABS with TPE
- Screws: stainless steel V2A (AISI 304L)

Tightness:

- gastight and watertight to 1.0 bar

Tests/Standards:

- DVGW VP 601

FEATURES

Item: Dichteinsatz für Rohbauteil

Hauff-Technik Swiss AG
Grabenackerstrasse 7
4702 Oensingen, Switzerland

Tel.: +41 62 206 00-70
Fax: +41 62 206 00-79

office@hauff-technik.ch