

Outer sealing element module 4

for single-line building entry systems basic variant 1

FLFA1x100/80/0 DIN18533 A2

Article no.: 2500400002, GTIN: 4052487062336

Outer sealing element for ESH Basic - BV 1 with fixed/loose flange for buildings with a basement with waterproof sheeting for standing/pressing water load case to DIN 18533, W2.2-E. Suitable for holding bitumen or foil waterproof sheeting.



Picture may differ from selected product

FACTS

Advantages:

- Can be installed easily and quickly on-site

Scope of delivery:

- 1 piece Fixed/loose flange for dowelling
- 4 pieces wall fastenings SXR 10x80

Dimensions:

- Fixed flange OD: 420 mm
- Loose flange OD: 410 mm
- Thickness of fixed flange: 10 mm
- Thickness of loose flange: 10 mm

Properties:

- For buildings with a basement to DIN 18533 W2.2-E
- Holds waterproof sheeting (bitumen or foil)

Application range:

- DIN 18533 W1-E, DIN 18533 W2.1-E, DIN 18533 W2.2-E

Material:

- Stainless steel V2A (AISI 304L)

Tightness:

- gastight and watertight to 1.0 bar

FEATURES

Wall sleeve ID (mm) D1:	100
Fixed flange OD (mm) D2:	425
Loose flange OD (mm) D3:	415
Wall sleeve wall thickness (mm) S:	2

ACCESSORIES REQUIRED



Outer sealing element module 1