

# Fire protection kit S90

For core drills and wall sleeves

## HSS KB FR HRD



- **Special assembly pockets for the assembly of pads on one side**
- **Special assembly pockets for the assembly of pads on one side**

Gastight and watertight fire barrier meeting the requirements of fire resistance class S90 in accordance with DIN 4102-9 for installation in core drills and/or plastic wall sleeves for walls. The seal is created with the HRD press seal. The barrier is approved for use with all types of cable in wall openings up to Ø 300 mm.



Picture may differ from selected product

## FACTS

### Advantages:

- High degree of flexibility as regards subsequent assignment
- No additional wall attachments necessary
- No limits on individual cable diameters
- Weatherproof fire-stop pads

### Scope of delivery:

- Wall openings up to Ø 100 mm: 1 set of HVS pads for full assignment (without cable): 2x HVS-K-250, 3x HVS-KB-60
- Wall openings up to Ø 150 mm: 1 set of HVS pads for full assignment (without cable): 2x HVS-K-400, 3x HVS-K-250, 3x HVS-KB-60
- Stainless steel clamping strap
- 1 piece Identification sign


## Dimensions:

- Barrier thickness: min. 280 mm
- Wall thickness at and above: 150 mm
- For core drills ID: 70 - 300 mm
- For plastic wall sleeves ID: 80 - 300 mm

## Tests/Standards:

- DIBT approval Z-19.15-1906 to DIN 4102-9

## PICTURES



## ACCESSORIES REQUIRED



Lubricant



Assembly plate for fire-stop pads