


Plastic spiral conduit hose for cable entry system

Hateflex14090/3000B

Article no.: 3030366899, GTIN: 4052487233125



• A pressure-tight cable entry system (for up to 2.5 bar external pressure) can be created using the associated connection components.

Picture may differ from selected product

Flexible and very rugged plastic spiral hose. A pressure-tight cable entry system can be created with the associated connection components.

FACTS

Advantages:

- Empty conduit route without sleeve available up to 25 m
- Empty conduit system that can be built over
- Smooth inner surface for gentle cable pulling

Scope of delivery:

• Coils in lengths of 25 m (special lengths are available in 0.5 m sections)

Dimensions:

- ID: 91 mm ± 1 mm
- OD: 104 mm ± 1 mm

Properties:

- Peak compressive strength: 745 N
- Installation temperature: +5°C to +50°C
- Weatherproof and will not rot
- Resistant to brine and seawater
- Installation temperature from +5° to +50°C
- Weather-proof, UV-resistant and rot-resistant
- Resistant to brine and seawater

Material:

Hard PVC/soft PVC

Tightness:

• gastight and watertight to 2.5 bar

FEATURES

Length (m): 3.0

PICTURES





Tel. +49 7322 1333-0

Fax +49 7322 1333-999