

Always. Reliable. Tight.

## Standard press seal

sealing width 80 mm

# HSD200 1x114 b80 A2/EPDM55

Article no.: 1600400115, GTIN: 4052487041010



- **optical and tangible installation security due to integrated control opening**

For sealing new pipes to be installed or pipes that have already been laid in core drills or wall sleeves. Available for delivery for all standard pipe sizes.



Picture may differ from selected product

## FACTS

### Application range:

- DIN 18533 W1.1-E, DIN 18533 W1.2-E, DIN 18533 W2.1-E, DIN 18533 W2.2-E
- Waterproof concrete stress class 1, Waterproof concrete stress class 2

### Advantages:

- Generous sealing width for gentle seal
- Available from stock

### Dimensions:

- Sealing width: 80 mm

## Properties:

- U-profile: maximum stability for press segments

## Material:

- Press plates, screws and nuts: rust-free stainless steel V2A (AISI 304L)
- Rubber: EPDM

## Tightness:

- Gastight and watertight

## FEATURES

|  |     |
|--|-----|
| Wall sleeve/core drilled hole ID (mm): | 200 |
| Suitable for medium pipe OD from (mm): | 114 |
| Suitable for medium pipe OD to (mm):   | 119 |

## PICTURES

