

Always. Reliable. Tight.

## Basic insert - arranged side by side for buildings without a basement

### MSH Basic FUBO R5 EBTM

Article no.: 1551001183, GTIN: 4052487033596



- **Variable height adaptation to the finished floor level**

Gastight and watertight wall sleeve for floor multi-line building entry system MSH Basic - MB - R3 (R2, R5). Variable frame elements enable the wall sleeve to be adapted to the ultimate finished floor level once the floor has been installed. The flexible spiral hoses and the building entry system MSH Basic - MB - R3 (R2, R5). must be ordered separately.



Picture may differ from selected product

## FACTS

### Application range:

- DIN 18533 W1.1-E
- Waterproof concrete stress class 2

## Advantages:

- Seals all supply lines through one entry
- Continuous duct connection up to the main supply lines at the edge of the property
- All services are fed in separately
- The arrangement of the individual services is flexible

## Scope of delivery:

- Wall sleeve with installation fixture
- 6 (4, 10) x hexagonal screws M8x45 and washers for sealing services

## Properties:

- Also required for the MSH Basic FUBO - R3 (R2, R5): flexible KES systems

## Material:

- Wall sleeve frame parts: ABS
- Installation fixture: St37

## Tightness:

- Gastight and watertight to 1 bar

## Tests/Standards:

- DVGW VP 601

# FEATURES

Lines side by  
side: 5

# PICTURES



# ACCESSORIES REQUIRED



Seal insert for basiv insert



Cable entry systems