

Always. Reliable. Tight.

## Basic insert - arranged side by side for buildings without a basement

### MSH Basic FUBO SR4 EBTM

Article no.: 1551008000, GTIN: 4052487141338



- **Variable height adaptation to the finished floor level**
- **Water barrier flange at the four sleeve pipes and the installation fixture**

Gastight and watertight wall sleeve for floor multi-line building entry system MSH Basic - MBK - R4. Variable frame connection elements enable the wall sleeve to be adapted to the ultimate finished floor level once the floor has been installed. The flexible spiral hoses and the building entry system MSH Basic - MBK - R4 must be ordered separately.



Picture may differ from selected product

## FACTS

### Application range:

- DIN 18533 W1.1-E
- Waterproof concrete stress class 1, Waterproof concrete stress class 2

## Advantages:

- Seals all supply lines through one entry
- All services are fed in separately
- Continuous duct connection up to the main supply lines at the edge of the property
- The arrangement of the individual services is flexible
- The individual frame segments can be snapped together

## Scope of delivery:

- Wall sleeve with installation fixture

## Properties:

- Also required: flexible KES systems

## Material:

- Wall sleeve segments: ABS
- Installation fixture: St37
- Water barrier flange: EPDM

## Tightness:

- Gastight and watertight to 1 bar

## Tests/Standards:

- DVGW VP 601

## PICTURES



# ACCESSORIES REQUIRED



Seal insert for basic insert



Cable entry systems