

# System cover

with sleeve method for corrugated cable ducts

## HSI150 MA178 WR

Article no.: 2126010116, GTIN: 4052487173995



- **Mechanical fixing (bayonet) and sealing (clamping nut) act independently**
- **Bayonet system with backstop and counter screw connection (prevents self-opening)**
- **patented ring clip method**

For use in wall insert and plastic flange HSI150. For connecting corrugated cable ducts. The seal is created with the sleeve method, with a rubber sleeve being clamped onto both the system cover and the duct with clamping straps.



Picture may differ from selected product

## FACTS

### Advantages:

- Mechanically stable, flexible connection with system sleeve

### Scope of delivery:

- sleeve with clamping straps
- including ring clips

### Properties:

- FHRK-certified
- For the duct connection  $\varnothing a = 160$  mm, we recommend using the spacer HSI AH40 to extend the center distance when installing multiple HSI150 wall inserts



## Material:

- System cover: polycarbonate
- Clamping nut: PC/PBT blend
- Sleeve: EPDM
- Clamping straps: W4
- Ring clips: stainless steel

## Tightness:

- gastight and watertight to 0.5 bar

## FEATURES

Tube Ø (mm): 178

Manufacturer: JFC/Polypie

## PICTURES



## ACCESSORIES REQUIRED



Flexible socket wrench