

Membrane injection system

for buildings with a basement

MIS90D 1x24-52+2x7 L SET

Article no.: 3030300142, GTIN: 4052487220286

- Universal building entry with membrane injection system for drill holes in the most common types of wall
 - Controlled ejection of resin through slit membrane hose
 - Simultaneous sealing of power and communication services

For reliable sealing of all electricity and telecommunications lines without additional shrinking using a sealing sleeve.



Picture may differ from selected product

FACTS

Advantages:

- Quick to assemble in just a few minutes
- Not necessary to restore basement seal to DIN 18533
- Flexibility provided by sealing sleeve with segmented ring technology

Scope of delivery:

- 1 packing unit:
- 6 pieces MIS 90 including pre-mounted sleeve cap
- 6 pieces wall collars

Dimensions:

• For core drills ID: 92 - 102 mm

Application range:

- DIN 18533 W1-E, DIN 18533 W2.1-E
- Waterproof concrete stress class 1, waterproof concrete stress class 2

Material:

- Flange, counter-bearing, sleeve cap, wall rosette, membrane hose: EPDM
- Resin filler hose: PE
- Pipe: PVC-U
- Sealing tape: butyl
- Stainless steel clamping straps: V2A (AISI 304L)

Tightness:

• gastight and watertight to 1.0 bar

FEATURES

Number of cables/medium overall: 3
Number of cables/medium: 1
2
Suitable for medium pipe OD 24-52
(mm): 7
Overall lenght (mm): 1300
wall thickness (mm): 900 - 1.200
Packing unit: 6

PICTURES







ACCESSORIES REQUIRED



Tel. +49 7322 1333-0

Fax +49 7322 1333-999