

# Standard press seal

## with segmented ring technology

### HRD100 SG 1x24-52 b40 A2/EPDM

Article no.: 2700101000, GTIN: 4052487168038



- **segmented ring technology for adjustment to three or five different pipe diameters on site**

For sealing a water line or a power cable and communications lines in core drills or wall sleeves. Split design for sealing new cables to be installed or cables that have already been laid.



Picture may differ from selected product

## FACTS

### Advantages:

- Empty openings are blind sealed ex works
- split seal for retrofit installation
- available from stock

### Scope of delivery:

- Blind plugs
- 1 piece of lubricating stick

### Dimensions:

- Sealing width: 40 mm
- Press plates: 5 mm



## Properties:

- FHRK-certified

## Application range:

- Water exposure class DIN 18533: W1-E, W2.1-E and W2.2-E
- Waterproof concrete stress class 1 and 2

## Material:

- Press plates, screws, nuts and washers: rust-free stainless steel V2A (AISI 304L), (V4A (AISI 316L) on request)
- Rubber: EPDM

## Tightness:

- gastight and watertight
- radon tight

## FEATURES

|  |       |
|--|-------|
| Wall sleeve/core drilled hole ID (mm): | 100   |
| Number of cables/medium overall:       | 1     |
| Openings:                              | 1     |
| Carrier pipe $\varnothing_a$ (mm):     | 24-52 |

## PICTURES

