

Always. Reliable. Tight.

Standard press seal with segmented ring technology

HRD150 SG 3x22-54 b40 A2/EPDM55

Article no.: 2700104000, GTIN: 4052487000185



- **Segmented ring technology for individual adjustment to cable diameters on site**

For sealing cables in core drills or wall sleeves. Split design for sealing new cables to be installed or cables that have already been laid.



Picture may differ from selected product

FACTS

Application range:

- DIN 18533 W1.1-E, DIN 18533 W1.2-E, DIN 18533 W2.1-E, DIN 18533 W2.2-E
- Waterproof concrete stress class 1, Waterproof concrete stress class 2

Advantages:

- Empty openings are blind sealed ex works
- Split seal for retrofit installation
- Available from stock

Scope of delivery:

- Blind plug
- Lubricating stick

Dimensions:

- Sealing width: 40 mm
- Press plates: 5 mm

Material:

- Press plates, screws, nuts and washers: rust-free stainless steel V2A (AISI 304L); (V4A (AISI 316L) on request)
- Rubber: EPDM

Tightness:

- Gastight and watertight

FEATURES

Wall sleeve/core drilled hole ID (mm):	150
Number of cables overall:	3
Number of cables:	3
Cable OD (mm):	22 - 54

PICTURES

