

Always. Reliable. Tight.

Standard press seal

with super segmented ring technology and polymer press plates

HRK200 SSG 3x40-72 b40 PAGF/A4/EPDM55

Article no.: 3030300050, GTIN: 4052487223676



- **Super segmented ring technology for individual adjustment to cable diameters on site**
- **Segments with exact diameter marking**
- **Press plates have form-fit connections**

For sealing cables in core drills or wall sleeves. Split design for sealing new cables to be installed or cables that have already been laid.



Picture may differ from selected product

FACTS

Application range:

- DIN 18533 W1.1-E, DIN 18533 W1.2-E, DIN 18533 W2.1-E, DIN 18533 W2.2-E
- Waterproof concrete stress class 1, Waterproof concrete stress class 2

Advantages:

- Split seal for retrofit installation
- Available from stock

Scope of delivery:

- Blind plug (if there is more than one cable entry)
- Cleaning cloth
- Knife
- Lubricating stick

Dimensions:

- Sealing width: 40 mm
- Press plates with reinforcement ribs: 20 mm

Material:

- Press plates: glass fibre reinforced polyamide
- Rubber: EPDM
- Screws and nuts: rust-free stainless steel V4A (AISI 316L)

Tightness:

- Gastight and watertight

FEATURES

| | |
|--|---------|
| Wall sleeve/core drilled hole ID (mm): | 200 |
| Number of cables: | 3 |
| Application range cable diameter: | 40 - 72 |
| Packing unit (pieces): | 8 |

PICTURES

