

Single-line building package

for buildings with a basement

ESH PolySafe BHP

Article no.: 3030300035, GTIN: 4052487223515



 optical and tangible installation security due to integrated control opening

Building package in the form of a single-line building entry system suitable for gas, water or power supplies - can used in all common types of wall.



Picture may differ from selected product

FACTS

Advantages:

- Can be installed easily and quickly on-site
- Continuous duct connection possible

Scope of delivery:

- 1 piece Single-service building entry system ESH PolySafe GV1
- 1 piece Outer sealing element ESH PolySafe M6.2
- 1 piece Insulation disk MSH PolySafe M3
- 1 piece sealing element for drinking water SDW 1x32/40/50
- 1 piece sealing element for electricity SDE 1x26-29/36-39/43-46/48-51
- 1 piece sleeve cap MS78U 1x24-52 for electricity or water
- 1 piece Pipe connection/extension set 4-piece
- 1 piece GMT35 lubricant





Dimensions:

- Compatible with core drill/wall sleeve ID: 99 103 mm
- Sleeve pipe OD: 75 mm, 600 mm long
- maximum wall thickness: 500 mm

Properties:

DVGW-certified

Application range:

- DIN 18533 W1-E, DIN 18533 W2.1-E
- Waterproof concrete stress class 1, waterproof concrete stress class 2

Tightness:

- gastight and watertight to 1.0 bar
- radon tight

Tests/Standards:

• DVGW VP 601

FEATURES

Packing unit: 10

PICTURES



Tel. +49 7322 1333-0

Fax +49 7322 1333-999