

# basic component

## Fibre optic handover system

# 2LINE G-BOX GBT GU

Article no.: 3030354822, GTIN: 4052487234153

For installation in all common ways (street, pavement area or customer plot).



Picture may differ from selected product

## FACTS

### Advantages:

- Sabotage-proof lid closure – can only be opened using special keys
- Suitable for use in high-traffic areas
- Height-adjustable

### Scope of delivery:

- Includes lid (plastic\* or cast)
- 2 pieces Tri-Head security bolts
- 2 pieces cover caps for Tri-Head security bolts
- \*Standard label "2LINE G-BOX": special label possible on request

## Dimensions:

- Overall height: 480 - 580 mm
- Lid dimensions: 157 x 157 mm
- Height adjustment: 100 mm

## Properties:

- Corrosion-resistant
- Sealed ready for installation
- Dimensions to DIN 3581
- Rattle-proof and maintenance-free
- Sealed ready for installation

## Application range:

- 4 connections for micropipes in sizes 7, 10, 12 mm
- Can hold 4 fibre optic cables between 0.5 - 8.0 mm (accessory required)

## Material:

- Cast lid: EN-GJL-250 (GG25)
- Plastic lid: glass fibre reinforced polyamide (PA-GF)
- Top section: glass fibre reinforced polyamide (PA-GF)
- Bottom section: ABS
- Screws: stainless steel V2A (AISI 304L)

## Tests/Standards:

- Manufactured in accordance with DIN 3580
- In accordance with DVGW VP310-2
- Verified lid load: 20 metric tons (cast)
- Verified lid load: 12.5 metric tons (plastic)

# FEATURES

: GU

# PICTURES



# ACCESSORIES REQUIRED



sealing case