

basic component

Fibre optic handover system

2LINE G-BOX GBT GU

Article no.: 3030354822, GTIN: 4052487234153

For installation in all common ways (street, pavement area or customer plot).



Picture may differ from selected product

FACTS

Advantages:

- Sabotage-proof lid closure can only be opened using special keys
- Suitable for use in high-traffic areas
- Height-adjustable

Scope of delivery:

- Includes lid (plastic* or cast)
- 2 pieces Tri-Head security bolts
- 2 pieces cover caps for Tri-Head security bolts
- *Standard label "2LINE G-BOX": special label possible on request

Dimensions:

Overall height: 480 - 580 mm
Lid dimensions: 157 x 157 mm
Height adjustment: 100 mm

Properties:

- Corrosion-resistant
- Sealed ready for installation
- Dimensions to DIN 3581
- Rattle-proof and maintenance-free
- Sealed ready for installation

Application range:

- 4 connections for micropipes in sizes 7, 10, 12 mm
- Can hold 4 fibre optic cables between 0.5 8.0 mm (accessory required)

Material:

- Cast lid: EN-GJL-250 (GG25)
- Plastic lid: glass fibre reinforced polyamide (PA-GF)
- Top section: glass fibre reinforced polyamide (PA-GF)
- Bottom section: ABS
- Screws: stainless steel V2A (AISI 304L)

Tests/Standards:

- Manufactured in accordance with DIN 3580
- In accordance with DVGW VP310-2
- Verified lid load: 20 metric tons (cast)
- Verified lid load: 12.5 metric tons (plastic)

FEATURES

: GU

PICTURES



ACCESSORIES REQUIRED



sealing case

Tel. +49 7322 1333-0

Fax +49 7322 1333-999