

Always. Reliable. Tight.

# Universal wall sleeve for any type of wall

## UFR300/500

Article no.: 2800030500, GTIN: 4052487154123



- **Integrated patch flange for the processing of plastic-modified bitumen thick coatings**

Facilitates sealing in all types of wall through a combination of integrated patch flange and 3-ribbed seal.



Picture may differ from selected product

## FACTS

### Application range:

- DIN 18533 W1.1-E, DIN 18533 W1.2-E, DIN 18533 W2.1-E
- Waterproof concrete stress class 1, Waterproof concrete stress class 2

## Advantages:

- Lightweight
- Simple installation in the formwork
- Can be cut to length on site
- Can be used in all types of wall including element constructions

## Scope of delivery:

- 2 closing covers

## Properties:

- Break-resistant, inherently stable
- Sealed ready for installation

## Material:

- Pipe: PVC-U
- Integrated patch flange: ABS
- 3-ribbed seals: EPDM
- Closing cover: PE

## Tightness:

- Gastight and watertight

## FEATURES

Wall sleeve ID (mm) D1: 300

Wall sleeve OD (mm) D2: 316

Patch flange OD (mm) D4: 436

Patch flange OD (mm) d3: 472

Wall thickness (mm): 500

## PICTURES

