

Always. Reliable. Tight.

Universal wall sleeve for any type of wall

UFR100/300

Article no.: 3030300247, GTIN: 4052487216128



- **Integrated patch flange for the processing of plastic-modified bitumen thick coatings**

Facilitates sealing in all types of wall through a combination of integrated patch flange and 3-ribbed seal.



Picture may differ from selected product

FACTS

Application range:

- DIN 18533 W1.1-E, DIN 18533 W1.2-E, DIN 18533 W2.1-E
- Waterproof concrete stress class 1, Waterproof concrete stress class 2

Advantages:

- Lightweight
- Simple installation in the formwork
- Can be cut to length on site
- Can be used in all types of wall including element constructions

Scope of delivery:

- 2 closing covers

Properties:

- Break-resistant, inherently stable
- Sealed ready for installation

Material:

- Pipe: PVC-U
- Integrated patch flange: ABS
- 3-ribbed seals: EPDM
- Closing cover: PE

Tightness:

- Gastight and watertight

FEATURES

| | |
|--------------------------|-----|
| Wall sleeve ID (mm) D1: | 100 |
| Wall sleeve OD (mm) D2: | 110 |
| Patch flange OD (mm) D4: | 210 |
| Patch flange OD (mm) d3: | 227 |
| Wall thickness (mm): | 300 |

PICTURES

