

Always. Reliable. Tight.

Universal wall sleeve for any type of wall

UFR200/250

Article no.: 3030300260, GTIN: 4052487221337



- **Integrated patch flange for the processing of plastic-modified bitumen thick coatings**

Facilitates sealing in all types of wall through a combination of integrated patch flange and 3-ribbed seal.



Picture may differ from selected product

FACTS

Application range:

- DIN 18533 W1.1-E, DIN 18533 W1.2-E, DIN 18533 W2.1-E
- Waterproof concrete stress class 1, Waterproof concrete stress class 2

Advantages:

- Lightweight
- Simple installation in the formwork
- Can be cut to length on site
- Can be used in all types of wall including element constructions

Scope of delivery:

- 2 closing covers

Properties:

- Break-resistant, inherently stable
- Sealed ready for installation

Material:

- Pipe: PVC-U
- Integrated patch flange: ABS
- 3-ribbed seals: EPDM
- Closing cover: PE

Tightness:

- Gastight and watertight

FEATURES

Wall sleeve ID (mm) D1:	200
Wall sleeve OD (mm) D2:	214
Patch flange OD (mm) D4:	311
Patch flange OD (mm) d3:	336
Wall thickness (mm):	250
Packing unit (pieces):	5

PICTURES

