


Stainless steel wall sleeve with puddle flange

for setting in concrete

FUM1x1000/150/150 A2

Article no.: 912520300, GTIN: 4052487022439

Puddle flange serves as water barrier and creates a force-fit connection.



Picture may differ from selected product

FACTS

Advantages:

- Simple installation in the formwork
- Also available with multiple entries and in a variety of diameters, resulting in compact construction

Scope of delivery:

• With closing covers on both sides

Dimensions:

• Flange OD equivalent to the corresponding wall sleeve ID + approx. 210 mm (for one entry, see the brochure for detailed information)



Properties:

FHRK-certified

Application range:

• Waterproof concrete stress class 1, waterproof concrete stress class 2

Material:

- Wall sleeve: stainless steel V2A (AISI 304L) or V4A (AISI 316L)
- Closing cover: PE

Tightness:

• gastight and watertight

FEATURES

Wall sleeve ID (mm): 1000
External diameter of flange (mm): 1208
Wall sleeve wall thickness (mm) 4
S: 4
Lenght (mm): 300

Hauff-Technik GmbH & Co. KG Robert-Bosch-Straße 9 89568 Hermaringen, GERMANY

office@hauff-technik.de

Tel. +49 7322 1333-0

Fax +49 7322 1333-999