


# **Membrane injection system**

for buildings without a basement

MIS40S 2x5-7 Set10

Article no.: 3030380167, GTIN: 4052487229883



- Controlled ejection of resin through slit membrane hose
- Sealing lips ensure gentle seal for media lines

Suitable for sloping entry through the wall or floor slab.



Picture may differ from selected product

### FACTS

#### **Advantages:**

- Quick to assemble in just a few minutes
- Not necessary to restore basement seal to DIN 18533

#### Scope of delivery:

- 1 packing unit:
- 10 pieces MIS 40S
- 10 pieces wall terminator element
- 10 pieces 2-component resin RESINATOR, 150 ml
- 1 piece quick tensioning device MIS40 SVS

#### **Dimensions:**

- For core drills ID: 40 50 mm
- Overall length: 1300 mm

#### **Application range:**

- DIN 18533 W1-E
- Waterproof concrete stress class 1, waterproof concrete stress class 2

#### **Material:**

- Flange and counter-bearing
- Resin filler hose: PE
- Pipe: PVC-U
- Wall terminator element: Flame-retardant polycarbonate
- Fast arrangement fixture: glass fibre reinforced polyamide/ABS

#### **Tightness:**

• gastight and watertight to 1.0 bar

### FEATURES

Number of cables/medium:	2
Suitable for medium pipe OD (mm):	5 - 7
Overall lenght (mm):	1300
wall thickness (mm):	200 - 1.200

### PICTURES



## ACCESSORIES REQUIRED



Quick tensioning device

office@hauff-technik.de