


Membrane injection system

for buildings with a basement

MIS60D 1x6-12 BL1300 Set10

Article no.: 3030391740, GTIN: 4052487230728



- Controlled ejection of resin through slit membrane hose
- Sealing lips ensure gentle seal for media lines

For existing buildings with a basement for reliable sealing of standard water lines.



Picture may differ from selected product

FACTS

Advantages:

- Quick to assemble in just a few minutes
- Not necessary to restore basement seal to DIN 18533
- Variety of seal inserts for variable configuration

Scope of delivery:

- 1 packing unit:
- 10 pieces MIS 60D including pre-mounted seal insert
- 10 pieces wall terminator element (only for communication variant)
- 10 pieces wall collar (only with electricity variant)
- 10 pieces 2-component resin RESINATOR, 150 ml
- 1 piece quick tensioning device MIS60 SVS



Dimensions:

- For core drills Ø: 62 65 mm
- For wall thicknesses: from 200 to 1200 mm

Application range:

- DIN 18533 W1-E, DIN 18533 W2.1-E
- Waterproof concrete stress class 1, waterproof concrete stress class 2

Material:

- Flange, seal insert, counter-bearing and adapter: EPDM
- Sealing tape: butyl
- Resin filler hose: PE
- Wall collar: PE
- Pipe: PVC-U
- Wall terminator element: Flame-retardant polycarbonate
- Fast arrangement fixture: glass fibre reinforced polyamide/ABS

Tightness:

- gastight and watertight to 1.0 bar
- radon tight

FEATURES

Number of cables/medium: 1

Suitable for medium pipe OD

(mm):

6 - 12

Overall lenght (mm): 1300

wall thickness (mm): 900 - 1.200

PICTURES







ACCESSORIES REQUIRED



Cartridge gun



Quick tensioning device

Tel. +49 7322 1333-0

Fax +49 7322 1333-999