


Membrane injection system

for buildings without a basement

MIS60S 4x5-7 BL1300 Set10

Article no.: 3030380178, GTIN: 4052487229777



- Controlled ejection of resin through slit membrane hose
- Sealing lips ensure gentle seal for media lines

Suitable for sloping entry through the wall or floor slab.



Picture may differ from selected product

FACTS

Advantages:

- Quick to assemble in just a few minutes
- Not necessary to restore basement seal to DIN 18533
- Variety of pre-mounted seal inserts for variable configuration

Scope of delivery:

- 1 packing unit:
- 10 pieces MIS 60S
- 10 pieces wall terminator element (only for communication variant)
- 10 pieces wall collar (only with electricity variant)
- 10 pieces 2-component resin RESINATOR, 150 ml
- 1 piece quick tensioning device MIS60 SVS

Dimensions:

- For core drills Ø: 62 65 mm
- Overall length: 1300 mm

Application range:

- DIN 18533 W1-E
- Waterproof concrete stress class 1, waterproof concrete stress class 2

Material:

- Flange, seal insert, counter-bearing and adapter: EPDM
- Resin filler hose: PE
- Wall collar: PE
- Pipe: PVC-U
- Wall terminator element: Flame-retardant polycarbonate
- Fast arrangement fixture: glass fibre reinforced polyamide/ABS

Tightness:

• gastight and watertight to 1.0 bar

FEATURES

Number of cables/medium: Suitable for medium pipe OD

5 - 7

Overall lenght (mm): 1300 wall thickness (mm): 200 - 1.200

PICTURES



ACCESSORIES REQUIRED



Cartridge gun



Quick tensioning device

Tel. +49 7322 1333-0

Fax +49 7322 1333-999