

# Fixed/loose flange wall sleeve galvanised

for setting in concrete for black tank

FLFE1x200/500 DIN18533 St-A3C

Article no.: 3030353479, GTIN: 4052487227056

For setting in concrete or mortar in walls, ceilings or floors.



Picture may differ from selected product

## FACTS

### Advantages:

- flexible wall thickness adjustment thanks to plastic wall sleeve
- Installation flush with formwork

### Scope of delivery:

- 1 piece Fixed/loose flange wall sleeve
- Fastenings for concrete
- Bolts and nuts
- 2 pieces closing covers

### Dimensions:

- for wall thicknesses of up to 500 mm
- Design according to DIN 18533 includes: underground structural components
- Standard fixed flange  $\varnothing a$  equal to the relevant wall sleeve  $\varnothing i$  + approx. 330 mm (for one passage)

### Application range:

- DIN 18533 W2.1-E, DIN 18533 W2.2-E

## Material:

- Fixed/loose flange wall sleeve steel galvanised (gv)
- Wall sleeve: plastic PVC-U
- Closing cover: PE
- Bolts and nuts: steel galvanised (gv)

## Tightness:

- gastight and watertight

## FEATURES

|                                 |     |
|---------------------------------|-----|
| Wall sleeve ID (mm) D1:         | 200 |
| Fixed flange OD (mm) D2:        | 530 |
| Loose flange OD (mm) D3:        | 520 |
| Wall sleeve wall thickness (mm) | 2   |
| S:                              |     |
| wall thickness (mm):            | 500 |

## PICTURES



## ACCESSORIES REQUIRED



Rubber inlays