

Fixed/loose flange wall sleeve made from stainless steel

for setting in concrete for black tank according to DIN 18533

FLFE1x350/0/365 DIN18533 A2

Article no.: 2500350365

For setting in concrete or mortar in walls, ceilings or floors.



Picture may differ from selected product

FACTS

Advantages:

- Tailor-made designs can also be produced
- Also available with multiple entries and in a variety of diameters
- Installation flush with formwork

Scope of delivery:

- 1 piece of fixed/loose flange wall sleeve
- Bolts and nuts M20 (DIN 18533)
- with closing covers on both sides

Dimensions:

- Standard fixed flange Øa equal to the relevant wall sleeve Øi + approx. 330 mm (for one passage)

Application range:

- Water exposure class DIN 18533: W1-E, W2.1-E and W2.2-E

Material:

- Fixed/loose flange wall sleeve: stainless steel V2A (AISI 304L) or V4A (AISI 316L)
- Closing cover: PE

Tightness:

- gastight and watertight

FEATURES

Wall sleeve ID (mm) D1:	350
Fixed flange OD (mm) D2:	680
Loose flange OD (mm) D3:	670
Wall sleeve wall thickness (mm) S:	3
Wall thickness (mm):	365

PICTURES



ACCESSORIES REQUIRED



Rubber inlays