

Always. Reliable. Tight.

Fixed/loose flange wall sleeve made from stainless steel

for retrofit dowelling for black tank according to DIN 18533

FLFA1x500/80/0 DIN18533 A2

Article no.: 2500400011

For dowelling with wall sleeves, core drills or breakthroughs.



Picture may differ from selected product

FACTS

Application range:

- DIN 18533 W2.1-E, DIN 18533 W2.2-E

Advantages:

- Tailor-made designs can also be produced
- Also available with multiple entries and in a variety of diameters

Scope of delivery:

- Fixed/loose flange wall sleeve
- Bolts and nuts M20 (DIN 18533)
- Fastenings for concrete

Dimensions:

- Design according to DIN 18533 includes: underground structural components. Standard fixed flange Øa equal to the relevant wall sleeve Øi + approx. 330 mm (for one passage; see brochure for details)
- Standard upper length: 80 mm

Material:

- Fixed/loose flange wall sleeve: stainless steel V2A (AISI 304L) or V4A (AISI 316L)
- Fastenings: V4A (AISI 316L)
- Closing cover: PE

Tightness:

- Gastight and watertight

FEATURES

Wall sleeve ID (mm) D1:	500*
Fixed flange OD (mm) D2:	830
Loose flange OD (mm) D3:	820
Optimal application range OD (mm):	370 – 420
Max. possible application range Ø (mm):	0 – 450
Wall sleeve wall thickness (mm) S:	4

PICTURES



ACCESSORIES REQUIRED



Rubber inlays