

# Single wall insert with foldable rubber sleeve

for setting in concrete and connecting corrugated cable ducts

## HSI150 1x1 KMA172/300

Article no.: 3030477598, GTIN: 4052487242158



- thanks to the folding sleeve method, no additional pipe components are required
- elastic and firmly anchored connection thanks to increased insertion depth, even if the cable duct hose is deflected
- inside connection option for system seals for cables




Picture may differ from selected product

For the direct connection of cable protection conduits (outside) and for connecting system seals for cables (inside).

## FACTS

### Advantages:

- defined insertion depth of the cable duct hose through stop in the sleeve
- Readily available for wall thicknesses 120 mm and above
- Quality mark: sealed ex works. Option to check for accidental or unauthorised opening of the closing cover
- Pressure-tight seal to the concrete through 3-ribbed seal, with two 3-ribbed seals from wall thicknesses of 150 mm and above



## Scope of delivery:

- 1 piece of pressure-tight system cover HSI150 DTS
- 1 piece of blind cover
- 2 pieces of HSI150 AH40 spacer
- 1 piece of clamping strap
- when connecting corrugated cable ducts, clip rings must be ordered separately. When ordering, please specify tube type and producer.

## Dimensions:

- Frame dimensions: 220x 220 mm
- Centre distance with spacer: 250 mm

## Properties:

- FHRK-certified

## Application range:

- Waterproof concrete stress class 1 and 2

## Material:

- Wall insert: ABS with TPE 3-ribbed seal
- Closing cover: ABS with TPE seal
- Adapter pipe: PVC
- Sleeve: EPDM
- Clamping straps: W4
- Blind cover: PP

## Tightness:

- gastight and watertight to 2.5 bar
- radon tight

## FEATURES

wall thickness (mm):	300
Pipe OD:	172

## PICTURES

